Original Research Article

Validating Visual Modflow Numerical Model To Predict Future

Impact Of Brine Disposal On Groundwater

Abstract

The aim of this research is to simulate the groundwater extraction and brine disposal<u>fate</u>. The Visual MODFLOW numerical model was used to predict the salt concentration emigration over time in an<u>groundwater</u>-aquifer. The main objective of this study is to verify and calibrate the Visual modflow software for predicting the impact of brine disposal on the groundwater salinity.

Keywords: Brine disposal; Desalination; Groundwater; Injection well; Visual MODFLOW

INTRODUCTION

Desalination is one of the non-conventional water resources where fresh water is produced from treatment of salt water. However, the negative impact of desalination process is the brine disposal which is a real environmental problem that should be considered and studied before constructing a desalination plant. The brine resulted from the desalination process is usually injected into a saline aquifer or discharged into the sea. The practice of disposing the rejected brine into the sea is common for plants located in coastal areas [1]. The problem of disposing the rejected brine into the sea may change increase seawater salinity leading to injuring plants and animals in the marine sanctuary [3, 5, 6]. In the case of disposing the rejected brine into the sen in a way that respects the environment. Nowadays, many mathematical models have been developed to simulate groundwater flow.

In this research, the laboratory experiment of [4] is used to calibrate the Visual MODFLOW (VMOD). Then four scenarios were proposed, designed and simulated to study the process of groundwater extraction and rejected brine injection water into a virtual aquifer using Visual modflow. The main objective of this

Commented [AFI]: The overall procedure of this study is
wrong. You have to respect the following steps:
1-Build the conceptual model,
2- Calibrate the model,
3-Validate the model
4-Use the model for prediction
Step 1 is missing.

Commented [AF2]: the abstract is too short. you should briefly talk about the method used and the silent results.

Commented [AF3]: There is no way for you to calibrate a software, but a model you built by that software. You may have a good idea, but a bad objective. You state two different objectives in this abstract; what do you really intend to do?

Commented [AF4]:

Commented [AF5]: don't use the same words as in the title

Formatted: Highlight

Formatted: Highlight

Formatted: Highlight

Formatted: Highlight

Commented [AF6]: how can you say that desalinisation is a water resources?

Commented [AF7]: What are you studying? Groundwater flow or brine disposal into aquifer?

Commented [AF8]: What do you mean by this? Explain it clearly and pay attention to the tense of verbs.

Commented [AF9]: You cannot calibrate VMOD, but a model that you have previously built to simulate the behaviour of an aquifer to a phenomenon

study is to calibrate and validate the Visual modflow software for predicting the impact of brine disposal

on the groundwater salinity.

Visual MODFLOW Model

Visual MODFLOW is a software developed by Waterloo Hydro geologic. The software is used to simulate three-dimensional groundwater movement and solute transport. Visual MODFLOW provides many numeric engines that perform the numeric calculations required to solve the finite difference scheme of groundwater flow and mass transport. SEAWAT is the numerical engine implemented in this study as it simulates three-dimensional, variable-density, unsteady groundwater flow in porous media. The density-dependent groundwater flow model is governed by the equation that developed by [2] as shown in Eq. (1)

$$\frac{\partial}{\partial x} \left(\rho K_{fx} \left[\frac{\partial h_f}{\partial x} \right] \right) + \frac{\partial}{\partial y} \left(\rho K_{fy} \left[\frac{\partial h_f}{\partial y} \right] \right) + \frac{\partial}{\partial z} \left(\rho K_{fz} \left[\frac{\partial h_f}{\partial z} + \left(\frac{\rho - \rho_f}{\rho_f} \right) \right] \right) = \rho s_f \frac{\partial h_f}{\partial t} + \theta \frac{\partial \rho}{\partial c} \frac{\partial c}{\partial t} - \underline{\rho} q_s \quad (1)$$

Where ρ is the fluid density, K_{fx}, K_{fy} and K_{fz} are freshwater hydraulic conductivity in the x, y and z direction, h_f is the equivalent fresh water head, ρ_f is the density of freshwater, S_f is the fresh water specific storage, θ is the porosity, C is the concentration of solute mass per unit volume of fluid, q_s is the volumetric flow rate of sources or sinks per unit volume of aquifer and t is time. The governing equation for solutetransport is given by Eq. (2):

$$\frac{\partial(\theta C)}{\partial t} = \nabla(\theta D. \nabla C) - \nabla(qC) \pm q_s C_s$$
(2)

Where:

D is the hydrodynamic dispersion coefficient tensor, q is specific discharge and

C_s is the solute concentration of water entering from sources or sinks.

Visual modflow calibration

VMOD model in the current research was calibrated with the experimental results conducted by [4] at Hydraulic Laboratory of Cairo University, Giza, Egypt. The experiment setup was a rectangular seepage tank with dimension of 1.42 m long, 0.1 m wide and 0.6 m high was used in the experimental work. An injection well of 10 cm width was inserted on the left side of the seepage tank with a screen of 10 cm width that located at 0.15 m from the base of the tank. While, a constant head boundary of 24.5 cm **Commented [AF10]:** This objective is not clear. You cannot calibrate a model that is not build! First, you have to build a model that predict the fate of brine water disposal into an aquifer, secondly, you would have to calibrate and validate that model.

Commented [AF11]: Where is the model? It would be difficult to follow you calibrating a model that does not exist. You should know that Visual modflow is a software and not a model.

So; present your conceptual model.

was maintained on the right side of the tank. A constant head reservoir containing brine water of 39,400

ppm concentration is was used to feed the injection well at a rate of 0.144 m³/day.

Models domain

It consists of one row, 29 columns and five layers. Dimensions of cells in column 1 are 0.02m * 0.05m and cells in layer 1 are 0.05m * 0.2m. The rest of the cells are 0.05 by 0.05m.

Initial and boundary conditions

Initial concentrations of model domain are set to be 800 mg/l and initial fresh water heads are all set to be 0.245 m. Brine is applied in column one and layer two through a well with injection rate 0.144 m³/day and of concentration equal to 39400 mg/l. A constant fresh water head boundary of 0.245 m and a constant concentration equal to 800 mg/l are specified at column 29 and layer one.

Model parameters

The parameters used in this model are hydraulic conductivity, specific yield, porosity and coefficient of effective molecular diffusion. The assigned values for these parameters were set to be 83 m/day, 0.27, 0.3 and 8.53*10⁻⁸ m²/min respectively.

Observation Points

Several observation points were constructed within the model domain as described in Table 1. The records obtained from the head and concentration observation points are required during the calibration process of the Visual MODFLOW model.

Table 1. Observation points locations

Observation Point No.	Observation point type	X (cm)	Y (cm)	Z (cm)
HOB1	Head	19.5	5	7.5
HOB2	Head	59.5	5	7.5
COB3	Salt conc.	29.5	5	2.5
COB4	Salt conc.	69.5	5	12.5
COB5	Salt conc.	109.5	5	7.5

Commented [AF12]: You should show the map or the figure of the designed area

Commented [AF13]: It is difficult to get you without a visual map

Commented [AF14]: Of what? Soil or water?

Commented [AF15]: What is the type of soil used? How many layers have you used and why? The soils was it disturbed or undisturbed? You previously talk of layer one, this mean that you have at least two layers. Here you give the properties of only one layer, what about the others layers?

Commented [AF16]: More description are required for the observation points. How are they monitored? How do you evaluate the water concentration in salt? Time steps were set to be 24 steps to represent both head and concentration values for six hours model run.

Results of calibration

The outputs of the model are illustrated in Fig. 1 and Fig. 2. A comparison between the results obtained from the VMOD and the laboratory experiment of [4] for the concentration observation points COB3, COB4 and COB5 is shown in Fig. 1.

The correlation coefficient obtained from the model for these observation points were equal to 0.991, 0.995 and 0.981 respectively. While, Fig. 2 shows a comparison between the results obtained from the VMOD and the laboratory experiment of [4] for the head observation points HOB1 and HOB2.The correlation coefficient obtained from the model for HOB1 equal to 0.901and for HOB2 equal to 0.835.



Fig.1. Comparison between results of Visual MODFLOW and laboratory experiment of [4] for COB3,

COB4 and COB5

4

Commented [AF17]: This is not the result of the calibration, but the result of your experiment. Calibration here mean that you are using the experimental result to refine your model result. But you did not present your model and it results.

Commented [AF18]: The main problem here is that you did not show how you got the set of data used to build the model. Data for calibration are from the lab experiment, what about the model data? This lead to a doubtful result. This figure has no meaning for

my point.



Fig. 2. Comparison between results of Visual MODFLOW and laboratory experiment of [4] for HOB1 and



Visual MODFLOW APPLICATIONS

It is important to design a discharge system for brine disposal that respects the environment and predict its effect on groundwater quality. Visual MODFLOW was used to detect the impact of brine disposal on the groundwater salinity by simulating four scenarios on the virtual aquifer as discussed in the following section.

Virtual coastal area

The dimensions of the virtual coastal area are 2500 m long, 1500 m wide and 150 m height as shown in Fig. 3. The groundwater level is at 50 m below ground surface and the aquifer thickness is 100 m. The east boundary of the aquifer (column 125) is the sea of concentration equal to 40000 mg/L. The discharge well is assigned at a fixed location 1020 m from sea, with a fixed discharge rate of 1200 m³/day and the injection well is located at spacing (*S*) from discharge well. The screen length of the injection well equal to 20m starting from 0 m above the base of the saline aquifer.

Commented [AF19]: The same observation made for figure 1 is valuable for figure 2. You cannot delineate the flow direction with only two observation points.

Commented [AF20]: For an original research, the scope of virtual aquifer is out of date. You should identify a real portion of a costal aquifer and experiment your research there.



Fig. 3. Virtual coastal area layout

Where:

Q_{inj} : is the rate of the injection well,

 Q_d : is the rate of the discharge well

C_{inj} : is the concentration of the injection well,

S: is the spacing between the injection and the discharge wells,

 C_i : is the initial concentration of the aquifer.

Visual Modflow simulation

Visual modflow was used to simulate the density-dependent flow and mass transport of the virtual coastal area. The model domain consists of 75 rows, 125 columns and five layers. Cells of layer 2, 3, 4 and 5 are 20 m by 20 m in the horizontal, and 20 m in the vertical while, cells in layer 1 are 20 m by 20 m in the horizontal, and 70 m in the vertical. A general head boundary condition (GHB) was assigned along the outside edged of the model domain (column 1, row 1 and row 52) with conductance equal to 16 m²/day. The parameters used in the model were the specific yield, the soil porosity and the effective molecular diffusion with values 0.27, 0.32 and 1.228*10⁻⁴m²/day respectively. Concentration and head observation points were constructed within the model domain at row 38, column 75, and layer **k** (according to the screen location of discharge well) as shown in Fig.4. Ten time steps were used to represent both head and concentration values for ten years model run.

Commented [AF21]: What is the scientific contribution of this research? This is virtual and nothing new here. I doubt that this can be helpful to the scientific community.

Commented [AF22]: Who is this layer?



Fig. 4. Numerical model showing vertical layout, (cross section for row 38)

Where:

OB: is the observation point

d: is the location of the screen of the injection well from the water table

d : is the location of the screen of the discharge well from the water table.

Simulated scenarios

In order to check the ability of the calibrated model in predicting the future impact of brine injection into

the aquifer for different cases, four runs have been conducted as shown in Table 2.

Table 2. Simulated scenarios used in VMOD application

Scenarios	Initial conc. of aquifer	Injection Conc. (mg/l)	Q _d (m³/day)	<i>Q</i> i (m³/day)	S (m)	K _x * (m/day)	d`∕d	к
	(mg/l)							
1	40000	80000	1200	600	100	33	0.6	3
2	40000	80000	1200	600	200	33	0.6	3
3	40000	80000	1200	600	300	33	0.6	3
4	40000	80000	1200	600	400	33	0.6	3

* is the hydraulic conductivity of the aquifer.

Application Results and discussions

The results of the simulated scenarios are shown in Fig.5 and Fig. 6.

Fig.5 is the design chart that has been developed by three design parameters, relative salt concentration (RSC), wells spacing (*S*), and simulation period (*T*). The Relative Salt Concentration at the discharge well (*RSC*) is given by Eq. (3):

$$RSC = \left(\frac{C_P - C_l}{C_l}\right) * 100 \tag{3}$$

Where: C_P is the predicted concentration from VMOD, C_i is the initial concentration and RSC is the relative salt concentration.

Fig. 5 shows that after 10 years of simulation, as the spacing increases by 300% the RSC decreases by about 66%. So this indicates that the RSC is **inversely proportion** to the spacing between the injection and discharge wells, but we have to take into consideration the available area for constructing the desalination plant and the cost of construction.



Fig. 5. Design chart for Qi=600 m³/day after 1, 5, 10 years of simulation

Fig. 6 represents the salt concentration distributions (shape of the salty plume) that develops around the injection well for a rate of injection equals 600 m³/day at spacing equals 100 m after 10 years of simulation. It also shows that the salt plume migrates downward due to the high density of the injected brine into the aquifer.



Formatted: Highlight

Fig. 6. Salt concentration distributions along x–z vertical plane after 10 years of simulation for injection rates 600 m³/day at S=100 m

CONCLUSIONS

From this study we can conclude that:

- There was a great agreement between the results of the Visual modflow and that of the laboratory experiment, where the correlation coefficient obtained from the model for the COB3, COB4 and COB5 were 0.991, 0.995 and 0.981 respectively. While for HOB1 and HOB2 were 0.901 and 0.835 respectivily.
- 2. Visual modflow model can be used as a useful tool for groundwater flow simulation.
- The Visual modflow can assist engineers and researchers in simulating and predicting the future impact of brine disposal on the groundwater salinity.
- The relative salt concentration of groundwater is inversely proportional to the spacing between the injection and discharge wells.
- 5. The salt plume migrates downward due to the high density of the injected brine into the aquifer.

Competing interests: no competing interests exist

REFERENCES

- El-Naas M H, Al-Marzouqi A H, Chaalal O. A combined approach for the management of desalination reject brine and capture of CO2. Desalination. 2010;251:70–74. https://doi.org/10.1016/j.desal.2009.09.141
- Guo W, Langevin C D. User's guide to SEAWAT: a computer program for simulation of threedimensional variable-density ground-water flow. USGS Techniques of Water Resources Investigations chap A7. 2002.
- Mansour S, Arafat H A, Hasan S W. Brine Management in Desalination Plants. In Desalination Sustainability. Elsevier. 2017;207–236. <u>https://doi.org/10.1016/B978-0-12-809791-5.00005-5</u>
- Nassar M K K, El-Damak R M, Ghanem A H M. Impact of desalination plants brine injection wells on coastal aquifers. In Environmental Geology. 2008;54:445–454. https://doi.org/10.1007/s00254-007-0849-9

Commented [AF23]: Visual Modflow was created for that. There is nothing new here

 Petersen K L, Frank H, Paytan A, Bar-Zeev E. Impacts of Seawater Desalination on Coastal Environments. In Sustainable Desalination Handbook: Plant Selection, Design and Implementation. Elsevier. 2018; 437–463. <u>https://doi.org/10.1016/B978-0-12-809240-8.00011-</u>

<u>3</u>

 Tularam G A, Ilahee M. Environmental concerns of desalinating seawater using reverse osmosis. Journal of Environmental Monitoring. 2007;9:805–813. <u>https://doi.org/10.1039/b708455m</u>