PRODUCTION OF BIOETHANOL FROM SELECTED LIGNOCELLULOSIC AGROWASTES

1 2

3

4

5 6

7

ABSTRACT

This study evaluated the ability of cassava peels, banana peels, orange peels and corn cobs hydrolysates to produce bioethanol. Fibre 8 fractions analysis was carried out using standard methods. The samples were pretreated with acid and base, followed by simultaneous 9 saccharfication and fermentation (SSF) for bioethanol production. During fermentation, pH, total titratable acidity, reducing sugar, microbial 10 load and bioethanol yield were determined. The reducing sugar yield for Aspergillus niger and Bacillus cereus were 30.28g and 13.35g for corn 11 cobs. The pH was observed to decrease during fermentation period with orange peels having the lowest pH of 2.6 after 240 hours of 12 fermentation using A. Niger and S. cerevisiae, when B. cereus and S. Cerevisiae were used the pH was observed to be 4.10. Total titratable 13 acidity showed increase in all the substrates, with corn cobs having the highest when B. cereus and S. Cerevisiae were used (1.62), followed by 14 cassava peels when A. niger and S. cerevisiae were used (1.52). Highest ethanol yield following simultenous saccharfication and fermentation 15 with A. niger and S. cerevisiae was obtained in corn cobs with 17.43g/100g, while orange peels gave the lowest with 8.02g/100g, the ethanol 16 yield from each substrates as well as the combined substrates were significantly different at $p \le 0.05$. The combined substrates (1:1:1:1) gave the 17

highest ethanol yield of 12.44g/100g using A. niger and S. cerevisiae. This study therefore revealed that A. niger had the highest bioethanol 18 yield using corn cobs as the carbon source, therefore it could be used for mass bioethanol production. 19 Key words: simultaneous saccharification, bioethanol, agrowastes, titratable acidity, reducing sugar 20 21 22 INTRODUCTION 23 24 Agricultural wastes have become an alternative raw material for bioethanol production, to prevent competition between food security and 25 ethanol production that the initial use of food crops for bioethanol has caused. lignocellulosic biomass can easily be utilized for biofuel 26 compared to food crops and holds the key to supplying society's basic needs for sustainable production of liquid transportation fuels without 27 impacting the nation's food supply (Alexander et al., 2012). 28 29 Lignocellulosic biomass is a major component of plants that provides them structure and is usually present in stalks, leaves and roots. 30 Lignocellulosic biomass consists mainly of three types of polymers: Cellulose (30% - 60%), hemicelluloses (20% - 40%) and lignin (10% -31 25%) which are interlinked to each other in a hetero-matrix (Nanda et al., 2014). Approximately 90% of dry matter lignocellulosics consists of 32 cellulose, hemicelluloses and lignin, whereas the rest comprises of ash and extractives (Rosa et al., 2013). Composition of lignocellulosic 33

biomass is influenced by the plant's genetic and environmental factors that vary considerably; however, the relative abundance of cellulose, 34 hemicelluloses and lignin depends on type of biomass and varies in different lignocellulosic biomass (Sanchez, 2009). 35

Cellulose $(C_6H_{10}O_5)_n$ is a homopolysaccharide composed of linear chains of β -D-glucose units linked by β -1, 4 glycosidic bond. These chains are linked by strong hydrogen bonding which forms the cellulose chains into microfibrils, making it crystalline in nature. These microfibrils are 37 bundled together to form cellulose fibres. Cellulose is made up of crystalline structure which is resistant to degradation and amorphous region 38 which is easy to degrade (Agbor et al., 2011). The cellulose fibres are embedded in an amorphous matrix of hemicelluloses, lignin and pectin. 39 Lignin and hemicellulose are present in the space between cellulose microfibrils in primary and secondary cell walls and middle lamellae (Van 40

and Pletschke, 2012). 41

36

Hemicelluloses are the branched heteropolymers consisting of pentose sugars (D-xylose and L-arabinose) and hexose sugars (D-mannose, D-42 glucose and D-galactose) with xylose being most abundant (Juturu and Wu, 2012). Hemicelluloses are composed of xylan, mannan, arabinan 43 and galactan as main heteropolymer (Beg et al., 2001). Xylan is the major structural component of the plant hemicelluloses and it is the second 44 most abundant renewable polysaccharide in nature after cellulose. Xylan represents approximately one-third of all the renewable organic carbon 45 on earth (Collins *et al.*, 2005). Xylan is a complex polysaccharide consisting of a backbone of xylose residues connected by β -1, 4-glycosidic 46 linkage along with traces of L-arabinose. The xylan layer with its covalent interaction to lignin and its non-covalent linkage with cellulose may 47 be essential in maintaining the integrity of cellulose in situ and in protecting the cellulosic fibers against degradation to cellulases (Beg et al., 48 2001). 49

Lignin is an aromatic polymer, consisting of phenyl propane units which are organized in to a large three dimensional network structure. Lignin 50 acts as glue and fills up the gap between and around cellulose and hemicelluloses in lignocellulosic biomass which binds them tightly. Lignin is 51 an amorphous heteropolymer which makes the cell wall impermeable, resistant against microbial and oxidative attack (Shahzadi et al., 2014). 52 The presence of lignin in lignocellulosic biomass makes difficult the release of monomer sugars from holocellulose (Nanda et al., 2014). 53 Extractives are low molecular weight and non-structural components of lignocellulosic biomass which are soluble in neutral organic solvents or 54 water. Extractives consist of biopolymers such as terpenoids, steroids, resin acids, lipids, waxes, fats, and phenolic constituents in the form of 55 stilbenes, flavanoids, tannins, and lignans. Generally, percentage of extractives is higher in leaves, roots and bark compared to steam wood 56 (Zhao et al., 2012); (Nascimento et al., 2013). 57

Bioconversion potential of lignocellulosic biomass from grasses, crop residues, forestry waste, and municipal solid waste into various value 58 added biological and chemical products is very essential and achievable. Accumulation of lignocellulosic biomass in large quantities presents a 59 disposal problem which results not only in deterioration of environment but also loss of valuable materials. This lignocellulosic biomass can be 60 used in paper manufacture, animal feed, biomass fuel production, and composting (Sanchez, 2009). Biotechnological transformation of 61 lignocellulosic biomass can make significant contribution for the production of organic chemicals. Over 75% of organic chemicals are 62 synthesized from five primary base chemicals which are ethylene, propylene, toluene, xylene and benzene (Howard et al., 2003). These 63 lignocellulosic biomass resources can also be used to produce various organic chemicals such as ethanol (Oberoi et al., 2010), acetone (Amiri et 64 al., 2014), butane (Al-Shorgan et al., 2012), bio-methane (Song et al., 2013) etc. Aromatic compounds might be produced from lignin whereas 65

the low molecular weight aliphatic compounds can be derived from ethanol produced by fermentation of sugars (glucose, mannose and xylose)

- 67 generated from saccharification of lignocellulosic biomass (Howard et al., 2003). Biotechnological conversion of lignocellulosic biomass in
- 68 various industrial products is cost effective and environmentally sustainable.
- 69 Lignocellulosic biomass are recalcitrant against enzymatic attack therefore, a pretreatment step is required which makes lignocellulosic biomass
- ⁷⁰ suitable for fermentation. Lignocellulosic biomass-derived sugars are economically attractive feedstock for large scale fermentation of different
- 71 chemicals. Sugars released after hydrolysis of cellulose and hemicelluloses are converted into different industrial products like ethanol, butanol,
- 72 glycerol, organic acids.
- 73

74 MATERIALS AND METHODS

75 Collection of samples

One thousand (1,000) grams each of fresh orange peels, cassava peels, banana peels, and corn cob were collected from Federal University of Technology, Akure (FUTA) farm and Oba Market in Akure South Local Government, Ondo State, located in south-west Nigeria. Akure lies about 70°15 North of the equator and 50°15 East Meridian. The city has a population of 588,000 which is 0.305% of Nigeria population based on 2006 population census. The samples collected from these locations were then sundried for three days after which they were milled. The dried samples were divided into two portions; the first portion was pretreated while the second was not.

81 **Pretreatment of Samples**

A two - stage process which combines the dilute acid pre-hydrolysis (DAPH-100-121) and alkaline delignificaton using NAOH as described by Olugbenga and Ibileke (2011) was used. Dry samples were treated with dilute sulfuric acid which involved the use of 1.25% (w/v) H₂SO₄ solution in a 1: 8, g : g, solid : liquid ratio. The one step dilute acid pre-hydrolysis (DAPH-100-121) was performed in an autoclave at 121^oC for 17min, after which the solids were collected and drained. The solids were then treated with 2% (w/v) sodium hydroxide solution in a solid: liquid ratio of 1: 20, g: g, at 120^oC for 90 min. after that, the residual solid material (Cellulose pulp) separated by filtration was washed with water to remove the residual alkali, and was dried at 50 ± 5^oC for 24 hours.

- 88
- 89
- 90

91 Sterilization, Preparation of Culture Media and Isolation

All glass wares (Petri dishes, beakers, conical flasks) were washed thoroughly, air dried, sterilized in hot oven around 180°C for 2 hours. Nutrient agar (NA) and Potato dextrose agar (PDA) were prepared according to manufacturer's specifications and autoclaved at 121°C for 15 minutes and allowed to cool to 45°C before pour plating.

Six fold serial dilutions was carried out on collected agro waste samples and pour plated with molten nutrient agar and the potato dextrose agar media, cooled to 45°C. Nutrient agar plates were incubated at 37°C for 24 hours for bacteria and 28°C for 3 to 5 days for fungi on 97 potato dextrose agar plates respectively in triplicate before examination for microbial growth. The bacterial isolates were purified by streaking 98 on fresh sterile nutrient agar before sub culturing. Fungal isolates were also sub cultured to obtain pure isolates. The pure isolates were stored 99 temporarily on slants and kept at 4°C for further use (Fawole and Oso, 2012). Colony count was carried out on plates (in triplicates) by using 100 colony counter and expressed as colony forming unit for bacteria and spore forming unit for fungi respectively.

101 Starch hydrolysis test

This test was used to detect the ability of bacterial isolates to produce starch degrading enzymes. It was performed for fungi isolates also. Nutrient agar and potato dextrose agar were both prepared with 1% soluble starch for bacteria and fungi respectively. The media was sterilized, poured into sterile petri-dishes and allowed to solidify. Bacterial isolates were inoculated onto the surface by streaking after which incubation at 37°C for 24 hours, while fungi isolates were inoculated by stabbing followed by incubation at ambient temperature for 3 days. After incubation, the plates were flooded with iodine; positive results were indicated by a clear zone around the colony which implies that starch was hydrolyzed, while a blue black coloration indicated a negative result (Fawole and Oso, 2001).

108

109 Determination of cellulose, Hemicellulose and lignin

110 The method of AOAC (2012) was used as described by Ververis *et al.* (2002). The substrates were analyzed for cellulose, hemicellulose 111 and acid insoluble lignin which were done before and after pretreatment. Cellulose was determined using a colorimetric method with the anthrone reagent. Ground samples were treated and boiled at 100° C with a mixture of nitric/acetic acid (1: 8, v/v) for 1 hr to remove lignin, hemicelluloses and xylosans after successive cetrifugations, and diluted with 67% H₂SO₄ (v/v). Cellulose was then determined at 620nm using cold anthrone reagent.

Hemicellulose and lignin contents of the substrates were determined as follows; the residue from above containing Hemicellulose and lignin was then boiled with 5 ml of 72% (w/w) H_2SO_4 solution for 4.5 hours in order to hydrolyze the hemicellulose. The suspension remaining after the above treatment was filtered through a crucible and the solid residue dried at 105°C for 24 hours and weighed (W1). The residue was then transferred to a preweighed dry porcelain crucible and heated at 600°C for 5 hours. After cooling down, it was weighed (W2). Acid insoluble lignin was then calculated by the difference (W1-W2).

The filtrate from the H_2SO_4 treatment that contained the sugars released from hemicellulose was thoroughly stirred and homogenized. Glucose (C1) and reducing sugar (C2) concentrations in the filtrate were determined. Following these measurements, the hemicellulose content was then calculated from the following equation:

123
$$\%\left(\frac{w}{w}\right)$$
 hemicellulose = $\left\{\frac{W}{s}\right\} \times (C2 - C1)X\left\{\frac{v}{M}\right\}X$ 100 Equation 1

Where; W= molecular weight ratio of the polymer and monomer pentose, S= saccharification yield, C2= determined reducing sugars concentration (g/L), C1= glucose concentration (g/L), V= total volume of sugar solution (L), M = dry weight of the sample (g).

126 Microbial hydrolysis

One hundred (100) grams of each pretreated substrates was weighed in duplicates into 1000ml conical flasks and made up to mark with distilled water, corked and sterilized at 121° C for 15 min. sterile distilled water was added to the flasks to final volume 1 liter and the flasks plugged with sterile cotton wool. After cooling, the medium was inoculated with 50ml of 36 hours culture of *Aspergillus niger* and *Bacillus cereus* separately; the pH of the medium was then adjusted to 5.0. Hydrolysis was carried out at room temperature for three days. A second uninoculated flask served as control. Samples were taken at the end of three days for reducing sugar determination (Abdullahi, 2013).

132

133

134 Determination of reducing sugar

The method of Olugbenga and Ibileke (2011) was used. Two mls of the hydrolyzed sample was placed in a test- tube and 1g of activated charcoal was added. The mixture was shaken thoroughly. The mixture was then filtered with filter paper until a colorless filtrate was obtained. One ml of filtrate was placed in a test-tube and two drops of alkaline DNS reagent were added and the tube was placed in boiling water for 5 min. the mixture was allowed to cool and the absorbance was measured at 540nm. This measurement was taken after three days. A standard curve of glucose was prepared and used to calculate the percentage reducing sugar.

140 Physicochemical analysis

141 The following physicochemical properties of each fermenting substrate were measured;

142 **Determination of pH**

- 143 The pH of each fermenting substrate was measured at 24 hours interval for seven days using a digital pH meter, standardized with buffer
- 144 of 7.0 the pH was then determined by inserting the electrode bulb into a sample from each fermenting substrate.
- 145
- 146
- 147

148 **Total titratable acid**

- 149 This was determined using the method of Lyumugabe et al. (2010) 10ml of the fermenting medium was transferred into a beaker,
- followed by the addition of 3 drops of phenolphthalein indicator. The sample was then titrated against 0.1M NaOH to an end point of a definite
- 151 pink colour. The volume of NaOH used was noted and the titratable acid percentage was calculated using the following formula;
- 152 TTA (%) = $V \ge 0.15$ equation 2
- 153 Where; V = Volume of NaOH.
- 154

155 **Preparation of inoculum**

156 *Aspegillus niger, Bacillus cereus* and *Saccharomyces cerevisiae* inocula were prepared by introducing slant cultures to 150ml of sterile

growth media contained in 500ml conical flasks. The flasks were incubated on a rotary shaker at 30° C for 96 hours (Ado *et al.*, 2009).

158 Standardization of inoculum (McFarland Turbidity standard)

Method modified by Cheesbrough (2006), was used to prepare the McFarland 0.5 turbidity standard which was used to measure the density of microbial cells. In this method, fifty milliliter (50ml) of a 1.175% (wt/vol) dehydrates Barium chloride (BaCl₂.2H₂O) solution was added to 99.4ml of 1% (vol/vol) sulfuric acid. McFarland standard tube was then sealed with Paraffin to prevent evaporation and stored in the dark at room temperature. The accuracy of the density of a prepared McFarland standard was checked by using a spectrophotometer with a 1cm light path. The 0.5 McFarland standards were vigorously agitated before use

164 Fermentation

Five sets of liquid state fermentation were carried out using the pretreated hydrolyzed samples. The hydrolysates from the above were transferred into another set of conical flasks and labeled correctly, covered, autoclaved at 121°C for 15 minutes and allowed to cool. The flasks were inoculated with *Saccharomyces cerevisiae* to carry out fermentation for ten days. The fermentation was then monitored from day 1, the pH of the hydrolysate containing *Saccharomyces cerevisiae* was adjusted to 5.0 and fermentation carried out at 30°C in a rotary shaker. The ethanol 169 yield was determined at 24 hours interval during fermentation. The fermentate was separated by centrifugation at 9000 rpm to separate the waste

170 from the supernatant (Abdullahi, 2013). All procedures were carried out in triplicates.

171 Distillation

It was carried out using a set up distillation apparatus. The fermented liquid was transferred into round bottom flask and placed on a heating mantle fixed to a distillation column enclosed in a running tap water. Another flask was fixed to the other end of the distillation column to collect the distillate at 78° C (standard temperature for ethanol production). Ethanol yield was then determined by obtaining the mass of the distillate in grams. Percentage ethanol was then determined by obtaining the specific gravity of the ethanol produced and using it to calculate the percentage (v/v) ethanol produced (Abdullahi, 2013)

177 Statistical analysis

Data are presented as mean \pm standard error (SE). Significance of difference between different treatment groups was tested using oneway analysis of variance (ANOVA) using SPSS (Statistical Package for Social Science) version 20 software. For all tests, the significance was determined at the level of P \leq 0.05.

181 **RESULTS**

182 Effect of acid pretreatment on cellulose, hemicellulose and lignin of the agricultural wastes.

183	Table 1 shows the effect of pretreatment on the cellulose; hemicellulose and lignin components of cassava peels, orange peels, banana peels and
184	corn cobs. The result indicates that there was significant difference ($p \le 0.05$) in the effect of acid pretreatments of the substrates. There was high
185	increase in cellulose content of corn cobs from 39.39% to 59.21%, while cassava peels showed an increase from 12.66% to 20.66%, orange peels
186	also showed cellulose content increment after pretreatment from 13.64% to 17.06% and banana peels which had the lowest showed an increase
187	from 2.09% to 9.43%. Hemicellulose content on the other hand decreased after pretreatment in cassava peels from 8.28% to 3.11%, in banana
188	peels from 11.46% to 1.33%, in orange peel from 6.29% to 4.23% and in corn cob from 43.34% to 16.95%. Lignin content of corn cobs reduced
189	drastically from 16.3% to 6.23%, similar decrease was also recorded for the lignin content of cassava peels, banana peels and orange peels.
190	

192 Reducing sugar produced by each substrates after 3 days of hydrolysis using *Aspergillus niger* and *Bacillus cereus*.

The reducing sugar produced by each substrate as well as the combinations of the substrates in ratio 1: 1: 1: 1 after three days of hydrolysis using *Aspergillus niger* is given in Figure 1. The result revealed that highest reducing sugar yield was obtained in corn cobs with 30.28g, followed by cassava peels with a yield of 26.36g, combinations of all the substrates (OCBC) gave a yield of 21.62g, and banana peels also gave a reducing sugar yield of 20.32g, while orange peels had the lowest with 16.23g.

Furthermore, figure 1 also shows the reducing sugar yield of each substrates and combinations of the substrates in ratio 1: 1: 1 after three days of hydrolysis using *Bacillus cereus*. However, the yield was considerably lower than what was obtained using *Aspergillus niger*.

199	Corn cobs gave the highest reducing sugar yield with 13.35g, followed by cassava peels with 11.14g, combinations of all the substrates (OCBC)							
200	gave a yield of 9.34g, and banana peels also gave a reducing sugar yield of 8.44g, while orange peels had the lowest with 5.88g.							
201								
202								
203								
204								
205	Table 1: Effect of acid pretreatment on cellulose, hemicellulose and lignin of the agricultural wastes							
	Parameter CpB (%) CpA (%) BpB (%) BpA (%) OpB (%) OpA (%) CcB (%) CcA (%)							

· /1

0 11 /1

			O					
Lignin	$9.34{\pm}0.04^{b}$	4.18±0.02 ^c	12.23±0.02 ^c	2.35 ± 0.01^{b}	2.25 ± 0.02^{a}	1.19±.03 ^a	$16.34{\pm}0.01^{d}$	$6.23{\pm}0.02^{d}$
Hemicellulose	$8.28{\pm}0.04^{\text{b}}$	3.11±0.00 ^b	11.46±0.04 ^c	1.33±0.03 ^a	6.29±0.13 ^a	4.23±0.02 ^c	$43.34{\pm}0.06^{d}$	$16.95{\pm}0.0^{\text{d}}$
Cellulose	12.66±0.01 ^b	20.66±0.30 ^c	2.09±0.03 ^a	9.43±0.022 ^a	13.64±0.01 ^c	17.0600±0.03 ^b	39.39±0.08 ^d	59.21±0.02 ^d

206

1 .

· 11

. . 1

Key: **CpB** (%) = Cassava peels before pre-treatment, **OpB** (%) = Orange peels before pre-treatment, **BpB** (%) = Banana peels before pre-treatment

- 209 CcB (%) = Corn cob before pre-treatment, CpA (%) = Cassava peels after pre-treatment, OpA (%) = Orange peels after pre-treatment,
 210 BpA (%) = Banana peels after pre-treatment, CcA (%) = Corn cob after pre-treatment.
- Values are means \pm Standard error of agricultural wastes. Values in the same row carrying the same superscript are not significantly different at (p \leq 0.05) using Duncan's New Multiple Range test.



219 Fig 1: Reducing sugar produced by each substrates after 3 days of hydrolysis using A. niger and B. cereus respectively.

Bars represent reducing sugar $(g/100g) \pm$ standard error, significant difference were taken at $(P \le 0.05)$ according to Duncan's New Multiple Range tests.

- Key: **OCBC** = Combinations of Orange peels /Cassava peels /Banana peels /Corn cob (Ratio 1:1:1:1) in grams

Changes in pH during fermentation of different agricultural wastes using

233 A. niger and S. cerevisiae.

234 The changes in pH during the fermentation of cassava peels, banana peels, orange 235 peels, corn cobs and the combinations of all the substrates in ratio 1: 1: 1: 1(OCBC) using A. 236 niger and S. cerevisiae are represented in Figure 2. A general decrease in the pH was 237 observed from the initial standardized pH of 5.0 as fermentation proceeded. Fermentation of 238 orange peels showed a decrease, with a pH of 3.0 after 7 days, cassava peels with a final pH of 4.0, banana peels with a pH of 4.0 after 7 days, and corn cobs with a final pH of 3.6. The 239 240 combinations of all the substrates in ratio 1:1:1:1 (OCBC) showed a decrease from the initial pH of 5.0 to 3.0 after 7 days of fermentation. 241

242

243 Changes in pH during fermentation of different agricultural wastes using

244 **B.** cereus and S. cerevisiae.

245 Figure 3 shows he changes in pH during the fermentation of cassava peels, banana 246 peels, orange peels, corn cobs and the combinations of all the substrates in ratio 1: 1: 1: 247 1(OCBC) using *B. cereus* and *S. cerevisiae*. A decrease in the pH was observed from the 248 initial standardized pH of 6.0 as fermentation proceeded. Fermentation of corn cobs showed a decrease with a final pH of 4.8 after 8 days, cassava peels recorded a decrease with a final pH 249 250 of 4.2, with the combinations of all the substrates in ratio 1:1:1:1 (OCBC) having a decrease 251 from the initial pH of 6.0 to 4.2, while orange peels had the lowest final pH of 4.0. However, 252 a slight fluctuation was observed from day 4.

- 253
- 254

255





281	Total titratable acidity during fermentation of different agricultural wastes
282	using A. niger and S. cerevisiae
283	The total titratable acidity during fermentation of each susbtrate using A. niger and S.
284	cerevisiae is shown in Figure 4. An increase in the TTA was observed from the initial TTA
285	as fermentation proceeded. Fermentation of corn cobs showed an increase in TTA, from an
286	initial TTA of 0.12% to 1.27% after 168 hours; banana peels showed an increase from 0.1%
287	initial to a final TTA of 0.9%, cassava peels also showed a very high TTA from 0.14% initial
288	to a highest of 1.5%. The combinations of all the substrates in ratio 1:1:1:1 (OCBC) showed
289	an increase in TTA from 0.09% to a highest of 1.23%.
290	
291	Total Titratable acidity during Fermentation of different Agricultural Wastes
292	using B. cereus and S. cerevisiae
293	Figure 5 shows the total titratable acidity during fermentation of different agricultural
294	wastes using B. cereus and S. cerevisiae. The result revealed that, as fermentation proceeded
295	from day zero to day seven, increase in the TTA was observed, corn cobs TTA was
296	conspicuously higher than the rest from an initial TTA of 0.1% to 1.7%, followed by
297	combinations of all the substrates in ratio 1:1:1:1 (OCBC) from initial TTA of 0.09% to
298	0.84%, while the lowest TTA was recorded for orange peels from 0.07% to 0.38%
299 300 301 302 303 304 305	
306	





Ethanol yield from different agricultural wastes using A. niger and

333 S. cerevisiae

334 Figure 6 shows the ethanol yield of the various substrates and their combination 335 during days of fermentation using A. niger and S. cerevisiae.. The ethanol yield was observed 336 to increase as the fermentation continued. Corn cobs had the highest initial yield of 3.22g 337 after 48 hours; followed by banana peels which had an initial yield of 2.21g, cassava peels 338 had 2.07g, while orange peels recorded the lowest with 1.30g. The combinations of all the substrates in ratio 1:1:1:1 (OCBC) also had ethanol yield of 1.90g after 48 hours of 339 340 fermentation, it was observed that corn cobs had the highest final ethanol yield of 17.43g, followed by cassava peels which gave a yield of 15.1g, while combinations of all the 341 342 substrates in ratio 1:1:1:1 (OCBC) gave a yield of 12.44g. Orange peels on the other hand 343 recorded the least ethanol yield of 8.03g

344

345

Ethanol yield from different agricultural wastes using B. cereus and

346 S. cerevisiae

347 The ethanol yield of the various substrates and their combination during days of 348 fermentation using *B. cereus* and *S. cerevisiae* are presented in Figure 7. The ethanol yield 349 was observed to increase as the fermentation proceeded, however it can be observed that the 350 ethanol produced was considerably lower than that produced by A. niger and S. cerevisiae. 351 The combinations of all the substrates in ratio 1:1:1:1 (OCBC) had the highest initial yield of 352 2.46g after 24 hours, followed by corn cobs which had an initial yield of 2.16g. Cassava peels 353 also had 1.91g, followed by banana peels with 1.41g, while orange peels had the lowest 354 initial yield of 0.82g after 24 hours. After 8 days of fermentation, corn cobs were shown to 355 have the highest final ethanol yield of 9.39g, followed by the combinations of all the 356 substrates in ratio 1:1:1:1 (OCBC) which gave a yield of 9.14g. However, it can be observed 357 that orange peels recorded the lowest ethanol yield of 5.50g after 7 days of fermentation.



Error bars: +/- 1 SE



Fig 6: Ethanol yield from different agricultural wastes using *A. niger* **and**

- 360 S. cerevisiae
- Key: OCBC = Combinations of Orange peels /Cassava peels /Banana peels /Corn cob
 (Ratio 1:1:1:1) in grams.



Error bars: +/- 1 SE

363

Fig 7: Ethanol yield from different agricultural wastes using *B. cereus* and *S. cerevisiae*Key: OCBC = Combinations of Orange peels /Cassava peels /Banana peels /Corn cob
(Ratio 1:1:1:1) in grams
369
370
371
372
373

Bacterial counts in Cfu/mL during fermentation of the agricultural wastes

The result of bacterial counts observed on nutrient agar from fermentation of orange peels, cassava peels, banana peels, corn cobs and combinations of all the substrates in ratio 1:1:1:1(OCBC) is presented in Table 2.The results showed that cassava peels had the highest initial count of 5.10×10^6 Cfu/mL, while orange peels had the lowest of 1.8×10^6 Cfu/mL. The combinations of all the substrates in ratio 1:1:1:1(OCBC) had the highest microbial load on Nutrient agar of 56.4×10^6 Cfu/mL after 6 days of fermentation, while orange peels was observed to have the lowest with 10.08×10^6 Cfu/mL after 9 days.

382

Fungal counts in Sfu/mL during the fermentation of the agricultural wastes

Table 3 shows Fungal Counts in Sfu/mL on PDA during the fermentation of the agricultural wastes, the result revealed that, banana peels had the initial highest count of 6. 7 x 10^5 Sfu/mL, while orange peels had the lowest of 2.1 x 10^5 Sfu/mL. After seven days of fermentation, the combinations of all the substrates in ratio 1:1:1:1(OCBC) had the highest fungal load of 5.2 x 10^5 Sfu/mL, followed by banana peel with 4.1 x 10^5 Sfu/mL, while orange peels recorded the lowest overall after several days of fermentation with 1.1 x 10^5 Sfu/mL

Table 2: Bacterial counts in Cfu/mL during fermentation of the agricultural wastes

FERMENTATION	Orange peels	OCBC Cfu/mL x 10^6	Cassava peels	Banana	Corn cob
DAYS	Cfu/mL $\ge 10^6$		Cfu/mL $\ge 10^6$	peelsCfu/mL x 10°	Cfu/mL ${ m x}~10^6$
0	1.8±0.12 ^g	4.90 ± 0.21^{ab}	5.10 ± 0.10^{b}	$3.70 \pm 0.30^{\circ}$	2.10 ± 0.10^{d}
1	$2.2\pm\!0.10^{bc}$	$5.20\pm\!\!0.00^{\rm f}$	5.50 ± 0.10^{e}	$3.90\pm\!\!0.20^{ab}$	$2.70\pm\!\!0.30^{gh}$
2	2.8 ± 0.40^{ef}	$5.80 \pm 0.10^{\circ}$	6.10 ± 0.00^{ab}	4.00 ± 0.30^{cd}	25.05±0.20 ^a
3	3.2 ± 0.08^a	2.61 ± 0.30^{bc}	$11.22 \pm 0.06^{\text{ef}}$	12.13 ± 0.10^{e}	$29.02 \ {\pm} 0.17^{f}$
4	$11.0\pm\!0.00^d$	50.8 ±0.17 ^{de}	14.13±0.40 ^{bc}	25.05 ± 0.15^{ef}	35 .08±0.10 ^g
5	21.2 ± 0.09^{b}	50.6 ±0.00 ^a	$27.08\pm\!\!0.17^{\rm f}$	29.18 ± 0.10^{b}	$48.17\pm\!\!0.27^{ab}$
6	26.01±0.12 ^e	$56.4 \pm 0.00^{\text{ef}}$	$31.05\pm\!\!0.14^{b}$	$31.10{\pm}0.13^{d}$	50.30±0.10 ^c
7	$29.12{\pm}0.10^{h}$	52.2±0.26 ^g	34.21 ± 0.06^{a}	$41.09\pm\!\!0.27^{bc}$	52.22 ± 0.17^{cd}
8	$33.42\pm\!0.00^{c}$	48.31±0.11 ^d	25.11 ± 0.26^{g}	52.03 ± 0.23^{de}	53.10 ± 0.10^{h}
9	22 .15±0.02 ^{ab}	36.12±0.00 ^{cd}	19.06 ± 0.15^{h}	$40.20\pm\!\!0.23^{gh}$	42.12 ± 0.20^{de}
10	10.08±0.14 ^{bc}	16.10 ± 0.00^{ab}	$14.10{\pm}0.00^{d}$	$21.00\pm\!\!0.20^a$	12.01±0.13 ^b

Values are means ± Standard error of agricultural wastes. Values in the same column carrying the same superscript are not significantly different

at $(p \le 0.05)$ using Duncan's New Multiple Range test.

Key: **OCBC** = Combinations of Orange peels /Cassava peels /Banana peels /Corn cob

(Ratio 1:1:1:1) in grams

FERMENTATIO	ORANGE DEELS	OCBC	CASSAVA	BANANA PEELS	CORN COB	401
N DAYS	PEELS Sfu/mL $\ge 10^5$	Sfu/mL $\ge 10^5$	Sfu/mL x 10^5	Sfu/mL x 10^5	Sfu/mL $\ge 10^5$	402
	•					403
0	2.1 ± 0.14^{bc}	2.90 ± 0.27^{b}	5.10 ± 0.20^{h}	6.70 ± 0.10^{d}	3.60 ± 0.22^{e}	404
1	$3.2 \pm 0.20^{\circ}$	$5.10\pm\!0.00^{ab}$	5.40 ± 0.12^{b}	$7.20 \pm 0.23^{\text{ef}}$	4.20 ± 0.15^{cd}	405
2	$3.8{\pm}0.30^{\rm f}$	5.80 ± 0.10^{gh}	$6.00 \pm 0.00^{\text{e}}$	8.00 ± 0.20^{cd}	4.50 ± 0.30^{a}	406
3	4.2 ± 0.16^{ab}	2.1 ± 0.20^{a}	$1.10 \pm 0.10^{\text{ef}}$	$1.90 \pm 0.10^{\rm g}$	1.20 ± 0.12^{b}	407
4	$1.10\pm\!\!0.10^{\rm f}$	3.0 ± 0.15^{e}	1.50 ± 0.21^{g}	2.6±0.33 ^a	1.3 ± 0.16^{d}	408
5	$2.3{\pm}0.20^{d}$	4.0 ± 0.30^{ef}	2.10 ± 0.10^{a}	2.8±0.12 ^e	$1.8 \pm 0.18^{\circ}$	409
6	$2.80\pm\!\!0.27^g$	4.8±0.00 ^d	2.90±0.15 ^{cd}	$3.20\pm\!\!0.00^{ab}$	$2.2\pm\!\!0.20^{gh}$	410
7	$2.9\pm\!\!0.37^h$	5.2 ± 0.20^{ab}	3.45 ± 0.00^{de}	4.10 ± 0.20^{b}	2.70±0.12 ^g	411
8	3.00 ± 0.10^{a}	4.9±0.20 ^{bc}	$2.7{\pm}0.28^{\rm f}$	5.30±0.23°	$1.72\pm\!\!0.30^h$	412
9	2.1±0.12 ^{bc}	3.2±0.00 ^{ab}	2.0±0.11 ^g	$4.20{\pm}0.20^{\rm f}$	1.52±0.20 ^g	413
10	1.10±0.14 ^f	1.8 ± 0.00^{d}	1.3±0.00 ^{ef}	$2.2\pm\!\!0.10^{ab}$	1.4 ± 0.00^{cd}	414

400 Table 3: Fungal counts in Sfu/mL during the fermentation of the agricultural wastes

Values are means \pm Standard error of agricultural wastes. Values in the same column carrying the same superscript are not significantly different at (p \leq 0.05) using Duncan's New Multiple Range test.

418

419 Key: **OCBC** = Combinations of Orange peels /Cassava peels /Banana peels /Corn cob

420 (Ratio 1:1:1:1) in grams

Comparison of commercial ethanol and bioethanol produced from different substrates The Comparison of conventional ethanol commercially available and bioethanol produced from different agro wastes substratesis presented in Table 4, all the ethanol produced and commercial ethanol appeared colourless, burns with blue flame and have refractive index of 1.36. Other properties such as relative density, boiling point, melting point, viscosity, and flash point showed little discrepancies.

Ethanol	Bioethaol	Bioethaol	Bioethaol	Bioethaol	Bioethaol	Commercial Ethanol
Properties	From cassava	From	From	From	From	
	peels	Banana peels	Orange peels	Corn cob	OCBC	
Appearance	Colourless	Colourless	colourless	colourless	Colourless	Colourless
				\sim		
Relative Density (g/cm ³)	0.756	0.773	0.777	0.782	0.774	0.789
Melting point (⁰ C)	-112	-114	-113	-112	-113	-114
			$\langle X \rangle$	~		
Boiling point(⁰ C)	78.40	78.36	78.38	78.37	78.40	78.37
Viscosity	0.0092	0.0122	0.0119	0.0060	0.0114	0.0012 pa s at 20^{0} C
Burning characteristics	Burns with blue	Burns with blue	Burns with blue	Burns with blue	Burns with blue	Burns with blue flame
	flame	flame	flame	flame	flame	
Refractive index	1.36	1.36	1.36	1.36	1.36	1.36
Flash point(⁰ C)	11	12	12	11	12	13-14

452 Table 4: Comparison of commercial ethanol and bioethanol produced from different substrates

453 Key: **OCBC** = Combinations of Orange peels /Cassava peels /Banana peels /Corn cob (Ratio 1:1:1:1) in grams

455 Key: **OCBC** = Combinations of Orange peels /Cassava peels /Banana peels /Corn cob (Ratio 1:1:1:1) in grams

DISCUSSION

The result of the acid pretreatment of the substrates was highly effective after the application of 459 NaOH. The result showed a drastic increase in the cellulose composition of the agro wastes with corn cob 460 having the highest amount of cellulose, and a subsequent decrease in the hemicellulose and lignin content. 461 This is a direct implication of the acid treatment that solubilized the hemi cellulosic fraction and increased 462 the diffusion of sodium hydroxide into the lignocellulosic structure, thus enhancing soda pulping and 463 liberating the cellulose fibres from lignin thereby causing the washing away of hemicellulose and lignin 464 during the filtration hence obtaining a solid residue with high content (Abo- State et al., 2014). The results 465 obtained in this study are in agreement with the findings of Chen et al. (2010) who reported similar increase 466 467 in cellulose and decrease in the hemicellulose and lignin contents of acid pretreated lignocellulosic substrates, and in contrast to that of Abo- State et al. (2014) who reported a decrease in all three 468 components, probably due to simultaneous pretreatment and hydrolysis. The high cellulose content and 469 decreased hemicellulose and lignin contents would allow for the enhancement of microbial saccharification 470 (Jeya et al., 2009). 471

It was observed in this study that the reducing sugar yield of A. niger was higher than B. cereus 472 yield. This was in agreement with Elsayed (2011) who showed a great difference between the cellulase 473 activity of Trichodema sp and Bacillus sp using rice straw residues as lignocellulosic substrate. This could 474 be attributed to the ability of Aspergillus niger to produce all components of cellulase complex, 475 endoglucanase, exoglucanase, and β- glucosidase in good proportions as well as production of other 476 enzymes such as xylanases or laccases in comparison to other enzyme producers (Arantes and Saddler 477 2010). Since the main part of the reducing sugar originated from the cellulose fraction, the difference in 478 reducing sugar yield observed for each substrate combination is invariably proportional to the initial 479 cellulose contained by each substrate after pretreatment (Taherzadeh et al., 2007). It could therefore be 480 inferred from the findings that the amount reducing sugar generated by hydrolysis was a function of how 481 482 effective the pretreatment stage was.

There was significant decrease in the pH of the fermenting media. This may be due to the release of 483 various organic acids from the utilization of the substrates. It was observed that the combinations of all the 484 substrates in ratio 1:1:1:1 (OCBC) showed the lowest pH in all the five fermentation sets after 7 days of 485 fermentation. This could be the result of better nutrient composition which favoured the growth of the 486 microorganisms and hence the production of metabolites. There was increase in total titratable acidity; this 487 could be as a result of utilization of free sugars by yeast and *Bacillus* (Akinyele et al., 2014). The result 488 however showed no direct relationship between the pH and TTA and this can be attributed to the production 489 of other metabolites by the microorganisms (Rajkovic et al., 2007). The observed variation in both pH and 490 TTA values for each substrate combination is a direct result of nutrient variation and hence metabolism of 491 the microorganisms. 492

The fermentation of the substrates using Saccharomyces cerevisiae showed that the yield of ethanol 493 494 is proportional to fermentation time, where the yield increased with increase in fermentation time, this correlation exist as a result of continuous utilization of the sugar by yeast, and this is in agreement with the 495 findings of Chen et al. (2010). It was also revealed that the combination of A. niger and S. cerevisiae gave 496 considerably gave higher ethanol yield in all the substrates as well as the substrates combination (OCBC), 497 100g of corn cob for instance gave an ethanol yield of 17.43g using A. niger and S. cerevisiae, and 9.39g 498 using B. cereus and S. cerevisiae. Cassava peel also recorded high ethanol yield of 15.1g, this was higher 499 than what was reported by Witantri et al. (2016) who produced bioethanol by utilizing cassava peels. This 500 501 may be due to the efficiency of the microorganisms employed during the hydrolysis stage. However, the relatively low yield observed during the fermentation of orange peel may be as a result of antimicrobial 502 activity of the peels that have been reported (Shetty et al., 2016), which slowed down the efficiency of the 503 microorganisms involved in hydrolysis and fermentation respectively, it could also be as a result of lignin 504 which prevented the free access of cellulose by the microorganisms (Subramanian, 2010). The combination 505 of all the substrates gave maximum ethanol yield of 12.44 less than 17.43 reported for corn cobs in this 506 507 study, this in contrast with the work of Elsayad (2013) who stated that the ethanol yield of each substrate is

directly proportional to its cellulose content. This could be attributed to a number of factors includingnutrient variation of the substrates.

Bacteria counts obtained from the fermentation of cassava peels, banana peels, orange peels and corn 510 cobs showed that cassava peel had the highest initial count on nutrient agar, while the combinations of all the 511 substrates in ratio 1:1:1:1(OCBC) had the highest microbial load on nutrient agar after 6 days of 512 fermentation, this was probably due to the fact that the combined substrates may contain varieties of 513 components, thus serving as a better source of nutrients for microbial growth than individual substrate. 514 These findings conform to the work of Lyumugabe et al. (2010) and Ibeabuchi et al. (2014) that reported 515 significant bacterial counts on nutrient agar for fermented products. The fungal counts of each substrate 516 during fermentation on PDA in this study showed that banana peels had the highest initial count, while 517 orange peel had the lowest, this could be attributed to the fact that, banana peels has been described as a 518 519 mycological medium (Essien et al., 2008). In addition it has the highest percentage of dietary fibres from this study, while orange peel possibly has antimicrobial property as reported by Shetty et al. (2016) which 520 invariably have adverse effect on fungal growth in the fermentation medium. 521

The comparison between the properties of cassava peels, banana peels, orange peels, corn cob and combinations of all the substrates in ratio 1:1:1:1(OCBC) with those of the conventional ethanol showed that, the flash point of the conventional ethanol ranges between 13° C and 14° C, slightly higher than 12° C noted for the correlation of both banana peels and orange peels, the properties of the alcohols shows that bioethanol derived from plant sources can serve similar purpose as their conventional counterparts.

527

528 Conclusion

This study established the efficiency of cassava peels, banana peels, orange peels, and corn cobs for bioethanol production, as well as the efficiency of selected cellulolytic microorganisms in the production process. *Aspergillus niger* was found to be more effective in cellulose hydrolysis than *Bacillus cereus*, thereby generating higher reducing sugar in each substrate and their respective combinations. Furthermore, it
was also observed that among the four substrates utilized, corn cob was found to be the most efficient
substrate for bioethanol production.

535

536 **REFERENCES**

- 537
- Abdullahi, M. (2013). Production of ethanol from cassava peels using *Zymomonas mobilis and Saccharomyces cerevisiae*. Department of Microbiology, Federal University of
 Tehnology, Minna. An unpublished B. sc. Thesis.
- 541
- Abo- state Mervate, A., Ahmed, M. E., Nour, S. E., Faharat, L. A. and Hekmat, M. R. (2014).
 Bioethanol production from rice straw enzymatically saccharified by fungal isolates, *Trichoderma viride* F94 and *Aspergillus terreus* F98. Soft. 3 :19-29
- 545
- Akinyele, B. J. (2014). Optimization of cellulase production by *Aspergillus flavus*NSPR017
 cultured on pretreated agro wastes. *Nigerian Journal of Microbiology*. 25: 2291-2301
- Ado, S. A., Olukotun, G. B., Ameh, J. B. And Yabaya, A. (2009). Bioconversion of cassava
 starch to ethanol in a simultaneous saccharification and fermentation process by cocultures of *Aspergillus niger* and *Saccharomyces cerevisiae. science world journal*, 4 (1):
 19-22.
- 553
- Agbor, V.B., Cicek, N., Sparling, R., Berlin, A. and Levin, D.B. (2011) Biomass
- 555 Pretreatment: Fundamentals toward Application. *Biotechnology Advances*, 29, 675-685.
- 556 http://dx.doi.org/10.1016/j.biotechadv.2011.05.005
- 557
- Alexander, V. G., Elena, G. K.and Arkady, P. S. (2012). Comparison of two methods for
 assaying reducing sugars in the determination of carbohydrate activities . *Internattional journal of analytical Chemistry*, 5(11): 1-4.
- 561

562	Al-Shorgani, N., Kalil, M. and Yusoff, W. (2012) Biobutanol Production from Rice Bran
563	and De-Oiled Rice Bran by Clostridium saccharoperbutylacetonicum N1-4.
564	Bioprocess and Biosystems Engineering, 35 , 817-826.
565	http://dx.doi.org/10.1007/s00449-011-0664-2
566	
567	Amiri, H., Karimi, K. and Zilouei, H. (2014) Organosolv Pretreatment of Rice Straw for
568	Efficient Acetone, Butanol, and Ethanol Production. <i>Bioresource Technology</i> , 152 ,
569	450-456. http://dx.doi.org/10.1016/i.biortech.2013.11.038
570	
570	Arantes, V. And saddler.J. N. (2010). Access to cellulose limits the efficiency of enzymatic
572	hydrolysis; the role of amorphogenisis. <i>Biotechnology Biofuels</i> , 3 (4): 1-11.
573	
574	A.O.A.C. (2012). Official methods of analysis of AOAC international 19 th Edition.
575	Gaithersburg, MD, USA, Association of Analytical Communities, pp; 35-60.
576	
577	Beg, Q.K., Kapoor, M., Mahajan, L. and Hoondal, G.S. (2001) Microbial Xylanases and
578	Their Industrial Applications: A Review. Applied Microbiology and Biotechnology,
579	56, 326-338. http://dx.doi.org/10.1007/s002530100704
580	
581	Cheesbrough, M. (2006). District laboratory practice in tropical countries. Part 2, pp 63-
582	130 And 267-332.
583	
584	Chen, Y., Dong, B., Weijun Q, Dongguang X. (2010) Xylose and cellulose fractionation from
585	corncob with three different strategies and separate fermentation of them to
586	bioethanol. Bioresource Technology 101 (2010) 6994-6999
587	Collins, T., Gerday, C. and Feller, G. (2005) Xylanases, Xylanase Families and
588	Extremophilic Xylanases. FEMS Microbiology Reviews, 29, 3-23.
589	http://dx.doi.org/10.1016/j.femsre.2004.06.005

590						
591	Elsayed, B. B. (2011). Bioethanol production from rice straw residues, Brazilian Journal of					
592	<i>Microbiology</i> , 44 (1) 225-234.					
593	Eriksson, KE.L. and Bermek, H. (2009) Lignin, Lignocellulose, Ligninase. Applied					
594	Microbiololgy Industrial, 373-384.					
595						
596	Essien, J. P. And Udotong, I. R. (2008). Amino acid profile of Biodrgraded Brewers spent					
597	Grains (BSG). Journal of Applied Science and Environmental Management, 12(1):					
598	109-111.					
599						
600	Fawole, M. O. and Oso, B. A. (2012). Laboratory Manual of Microbiology, Spectrum Books					
601	Limited. 2: 112-121.					
602	Hendriks, A.T.W.M. and Zeeman, G. (2009) Pretreatments to Enhance the Digestibility of					
603	Lignocellulosic Biomass. Bioresource Technology, 100, 10-18.					
604	http://dx.doi.org/10.1016/j.biortech.2008.05.027					
605	Horn, S., Vaaje-Kolstad, G., Westereng, B. and Eijsink, V.G.H. (2012) Novel Enzymes for					
606	the Degradation of Cellulose. Biotechnology for Biofuels, 5, 45.					
607	http://dx.doi.org/10.1186/1754-6834-5-45					
608						
609	Hossain, A. B. M. S, Ahmed, S. A, Ahmed, M. A., Farris, M. A. A., Annuar, M. S. M.,					
610	HAdeel, M. And Norah, H. (2011). Bioethanol fuel production from rotten					
611	banana as environmental waste management and suitable energy. African Journal					
612	of Microbiology. 5(6): 586-598.					
613						
614	Howard, R.L., Abotis, E., van Rensburg, E.L. and Howard, S. (2003) Lignocellulose					
615	Biotechnology: Issues of Bioconversion and Enzyme Production. African Journal of					
616	<i>Biotechnology</i> , 2 , 602-619. http://dx.doi.org/10.5897/AJB2003.000-1115					
617						
618	Ibeabuchi, J. C., Olaawuni, I. A., Iheagwara, M. C., Ojukwu, M. And Ofoedu, C. E. (2014)					
619	Microbiological Evaluation of 'Iru' and 'Ogiri-Isi' Used as Food Condiments.					

620	IOSR Journal of Environmental Science, Technology and Food Technology, 8(8):
621	45-50.
622	
623	Jeya, M., Zhang, Y. W., Kim, I. W. And Lee, J. K. (2009). Enhanced Saccarification of
624	Alkali-treated rice Straw by Cellulase from Trametes hirsute and Statistical
625	Optimization of Hydrolysis Conditions by RSM. Bioresource Technology, 100:
626	5155-5161.
627	
628	Juturu, V. and Wu, J.C. (2012) Microbial Xylanases: Engineering, Production and Industrial
629	Applications.BiotechnologyAdvances,30,1219-1227.
630	http://dx.doi.org/10.1016/j.biotechadv.2011.11.006
631	
632	Lyumugabe, F., Kamaliza, G., Bajyana, E., and Thonart P. H. (2010). Microbiological and
633	physico-chemical characteristic of Rwandese traditional beer "Ikigage, African
634	Journal of Biotechnology, 9(27): 4241-4246.
635	Levine, J.S. (1996) Biomass Burning and Global Change. In: Levine, J.S., Ed., Remote
636	Sensing and Inventory Development and Biomass burning in Africa, The MIT Press,
637	Cambridge, 35.
638	Malherbe, S. and Cloete, T.E. (2002) Lignocellulose Biodegradation: Fundamentals and
639	Applications. Reviews in Environmental Science and Biotechnology, 1, 105-114.
640	http://dx.doi.org/10.1023/A:1020858910646.
641	
642	Mussatto, S.I. and Teixeira, J.A. (2010) Lignocellulose as Raw Material in Fermentation
643	Processes. In: Mendez-Vilas, A., Ed., Current Research, Technology and Education,
644	Topics in Applied Microbiology and Microbial Biotechnology, Formatex Research
645	Center, Badajoz, 897-907.
646	Nanda, S., Mohanty, P., Pant, K., Naik, S., Kozinski, J. and Dalai, A. (2012) Characterization

647	of North American Lignocellulosic Biomass and Biochars in Terms of Their							
648	Candidacy for Alternate Renewable Fuels. Bioenergy Research, 6, 663-677.							
649	http://dx.doi.org/10.1007/s12155-012-9281-4.							
650								
651	Nanda, S., Mohammad, J., Reddy, S., Kozinski, J. and Dalai, A. (2014) Pathways of							
652	Lignocellulosic Biomass Conversion to Renewable Fuels. Biomass Conversion and							
653	Biorefinery, 4, 157-191. http://dx.doi.org/10.1007/s13399-013-0097-z							
654								
655	Nascimento, M.S., Santana, A.L.B.D., Maranhão, C.A., Oliveira, L.S. and Bieber, L. (2013)							
656	Phenolic Extractives and Natural Resistance of Wood. In: Chamy, R. and Rosenkranz,							
657	F., Eds., Biodegradation-Life of Science, InTech, Rijeka, Croatia, 349-370.							
658								
659	Oberoi, H.S., Vadlani, P.V., Brijwani, K., Bhargav, V.K. and Patil, R.T. (2010) Enhanced							
660	Ethanol Production via Fermentation of Rice Straw with Hydrolysate-Adapted							
661	Candida tropicalis ATCC 13803. Process Biochemistry, 45, 1299- 1306.							
662	http://dx.doi.org/10.1016/j.procbio.2010.04.017.							
663								
664	Olugbenga, A. O. and Ibileke, I. O. (2011) Bioethanol production from brewer's spent grain,							
665	bread wastes and corn fiber. African Journal of Food Science. 5(3): 148-155.							
666								
667	Rajkovic, M. B. Ivana, D. N. and Petrovic, A. (2007). Determination of Titratable Acidity in							
668	White Wine. Journal of Agricultural Sciences. 52(2): 169-184							
669								
670	Rosa Estela, QC.E. and Luis, FM.J. (2013) Hydrolysis of Biomass Mediated by Cellulases							
671	for the Production of Sugars. In: Chandel, A.K. and da Silva, S.S., Eds., Sustainable							
672	Degradation of Lignocellulosic Biomass-Techniques, Applications and							

673	Commercialization,	InTech,	Rijeka,	Croatia,	119-155.		
674	http://dx.doi.org/10.5772/53719						
675							
676	Sanchez, C. (2009) Lignocellulo	osic Residues: B	iodegradation a	nd Bioconversion	ı by Fungi.		
677	Biotechnology	Advances	,	27,	185-194.		
678	http://dx.doi.org/10.1010	6/j.biotechadv.20	008.11.001.				
679							
680	Shahzadi, T., Mehmood, S., Irsl	nad, M., Anwar,	Z., Afroz, A., Z	eeshan, N., Rash	id, U. and		
681	Sughra, K. (2014) Adv	ances in Lignoc	ellulosic Biotec	hnology: A Brie	f Review on		
682	Lignocellulosic Biomas	s and Cellulases	. Advances in B	ioscience and B	iotechnology,		
683	5 , 246-251. http://dx.doi	.org/10.4236/ab	b.2014.53031				
684							
685	Shetty, S. B., Prabu M. S., Sha	iji V,Bibin, T.,	Pathinettam K.T	., Deepak B., S	haista H. ,		
686	Sreeja S., Darshan D. (2016) Antimicrobial effects of Citrus sinensis peel extracts						
687	against dental caries bac	teria: An in vitr	o study. Journa	l of Clinical and			
688	Experimental Dentistry	8(1) DOI: 10.43	17/jced.52493				
689	Singhania, R.R., Sukumaran, R.	K., Patel, A.K.,	Larroche, C. and	d Pandey, A. (20	10)		
690	Advancement and Comp	parative Profiles	in the Production	on Technologies	Using Solid-		
691	State and Submerged F	ermentation for	Microbial Cellu	llases. Enzyme a	nd Microbial		
692	Technology, 46 , 541-549	9. http://dx.doi.o	rg/10.1016/j.enz	mictec.2010.03.0	010.		
693							
694	Song, Z., Yang, G., Han, X., Fe	ng, Y. and Ren,	G. (2013) Optin	nization of the Al	kaline		
695	Pretreatment of Rice	Straw for Enl	nanced Methan	e Yield. BioM	ed Research		
696	International, 2013, Art	icle ID: 968692.	http://dx.doi.org	g/10.1155/2013/9	068692		
697							

698	Subramanian, K. (2010). Biochemical conversion of rice straw into bioethanol-an exploratory
699	investigation. Unpublished research work.
700	
701	Taherzadeh, M.,J. and Karimi, K. (2007). Enzyme-based hydrolysis processes for ethanol
702	fromlignocellulosic materials: a review. Bioresources. 2(4): 707-738.
703	
704	Van Dyk, J.S. and Pletschke, B.I. (2012) A Review of Lignocellulose Bioconversion Using
705	Enzymatic Hydrolysis and Synergistic Cooperation between Enzymes-Factors
706	Affecting Enzymes, Conversion and Synergy. Biotechnology Advances,
707	30 , 1458-1480. http://dx.doi.org/10.1016/j.biotechadv.2012.03.002.
708	
709	Zhao, X., Zhang, L. and Liu, D. (2012) Biomass Recalcitrance Part I: The Chemical
710	Compositions and Physical Structures Affecting the Enzymatic Hydrolysis of
711	Lignocellulose. Biofuels, Bioproducts and Biorefining, 6, 465-482.
712	http://dx.doi.org/10.1002/bbb.1331
713	
714	
715	
716	
717	
718	
719	
720	
721	
722	
723	
724	
725	
120	

728	
729	
730	
731	
732	
733	
734	
735	
736	
737	
738	
720	
739	
740 741	
742	