# Use of Software for Image Analysis and Calibration of Automated Rain Simulator

# <sup>7</sup> 10 **ABSTRACT**

#### 11

1 2

3

4

5

6

**Aims:** To calibrate and evaluate a rain simulator, with automatic operation, as well as determine the average size, the effect of the height of the equipment (2.12; 2.42 and 2.72 m) and of the oscillations of the spray nozzle of the rain simulator (21, 29 and 40 oscillations min<sup>-1</sup>). Finally, to test and to compare the results of the count of drops by the software of analysis and processing of images Able Image Analyser, ImageJ and Safira.

**Study design:** The experimental design was completely randomized, with 3 x 3 x 3 factorial scheme, with three repetitions (81 units).

**Place and Duration of Study:** The research was conducted in a greenhouse belonging to the Rondonópolis Campus of the Federal University of Mato Grosso, in the municipality of Rondonópolis (MT).

**Methodology:** For the calibration tests, the rainfall simulator was adjusted according to the heights (2.12; 2.42 and 2.72 m) and oscillations (21, 29 and 40 oscillations min<sup>-1</sup>), followed by trays with a uniform layer of wheat flour, 2 cm thick, where the simulated raindrops were sprayed for a period of 4 seconds. From this procedure, the drops were dried, sifted, weighed and counted. Droplet analysis was performed using three image analysis software Able Image Analyser, ImageJ and Safira.

**Results:** The softwares Able Image Analyzer, ImageJ and Safira did not show any significant difference in counting of the number of drops. It was observed that in the oscillation factor in setting that if gets drops of larger size (21 oscillations min<sup>-1</sup>) the terminal velocity is also greater. In the height factor of the equipment, the drops presented larger sizes at the lower height (2.12 m). There are larger drops, higher terminal velocity as the height of the spray nozzle decreases, and higher kinetic energy value per unit area as the height of the spray nozzle increases. The range of drop sizes observed was 1.2 mm to 3.1 mm.

**Conclusion:** Although the software does not present significant differences, the ImageJ software proved to be more suitable as a research tool, since it has the license of free use and greater ease of use. Satisfactory results were obtained compared to natural rains in more than one combination of height and swings.

12

13 Keywords: artificial rain, calibration, scaling of drops, water erosion

14

# 15 **1. INTRODUCTION**

16

The study on the effects of water erosion on the ground is difficult to accomplish with the pluvial precipitation, because despite the weather forecasts, you have no control over the duration, intensity, distribution and type of precipitation [1–4].

The field monitoring under conditions of rain precipitation is the conventional method for studying the characteristics of runoff and sediment production. However, precise 22 measurements of the process of soil loss during natural rainfall are almost impossible [5–8].

An alternative that has been shown to be very effective is the use of rainfall simulators [9– 11].

The rain simulators are equipments into which the water is applied to experimental plots by sprinkling reproducing the pluvial precipitation and controlling the intensity and duration with precision [1, 10, 12].

Works with artificial rainfall simulators provide a relatively quick and economical way to obtain necessary information about erosion in a controlled environment and replicable [13– 15], providing valuable information about the runoff [16], water infiltration in the soil and erodibilidade [17, 18]. In addition to the impact of the physical properties of the soil [19], some studies also investigate the impact of vegetation cover [20].

The use of the equipment requires calibrations with the objective of identifying the combination of height and oscillations of the rainfall simulator that provide the adequate result in obtaining rainfall characteristics similar to natural ones.

36 It is essential the development of devices with latest technologies, built with of low cost 37 materials and reduced weight, but also meet the requirements of the characteristics that 38 send to natural rainfall. Existing rain simulation models, although they have evolved 39 considerably, are still structurally difficult to handle and transport, and still rely on their 40 mechanical operations.

The objective of the study is to calibrate the portable rainfall simulator with automatic operation, determine the effect of falling height, and estimate the terminal velocity of the drops. To Test and to compare drop count results with ImageJ, Safira and Able Image Analyzer image analysis and processing software.

45

# 46 2. MATERIAL AND METHODS

47

The research was conducted in a greenhouse belonging to the Rondonópolis Campus of the Federal University of Mato Grosso, in the municipality of Rondonópolis (MT), located geographically at latitude 16°27'49 "S, longitude 550°34'47" W, and altitude of 284 m. The region, according to the classification of Köppen, is of type Aw of the climate, hot and humid, characterized by the rainy season in the summer and dry in the winter [21].

The experimental design was completely randomized, with 3 x 3 x 3 factorial scheme, with three repetitions (81 units). The treatments were of three heights of the rain simulator equipment (2.72; 2.42 and 2.12 m), three water spray nozzle oscillations (21; 29 and 40 oscillations min<sup>-1</sup>) and three-image analysis software (ImageJ, Sapphire and Able Image Analyser).

The rain Simulator equipment built consisted of aluminum bars with mobile rods of three meters in height and three meters in length. The equipment has a windshield wiper motor voltage 12 V, with electronic system capable of oscillating movements. Mated to the engine, with the aim of fragmenting the drops on the plots, simulating a rain near natural condition, have a spray nozzle the Spraying Company 80-100 VEEJET® made in stainless steel, with opening angle range of 80°, operating a 34.47 the service pressure 3447.38 kPa and flow rate of 2.2 x 0.3 x 103 to 103 m3 s-1, Figure 1.

The water is pumped into the spray nozzle by a centrifugal pump with 367.749 power W, 220 V voltage, 147.1 kPa pressure and suction of 5 m. Hydraulic load is suctioned from the tank

67 and taken by 0.025 m polyethylene hoses. The working pressure used for promotion of the drops of rain is equal to 137.29 kPa, monitored by a pressure gauge and controlled by a 68 69 valve. The simplified scheme of the rain simulator system is presented in Figure 1.

70



Figure 1. Illustrative view of the rain simulator equipment; (01) tray; (02) retention valve; (03) gauge; (04) spray nozzle; (05) rain sensor; (06) aluminum movable rod; (07) windshield wiper motor.

The system has a voltage regulator, device that has the function to keep the output voltage

76 of the electrical circuit in order to balance it within the limits required by the electronic system 77 of the rain Simulator. The device has voltage regulator, coupled in your structure, a 78 frequency meter, electronic device capable of measuring the frequency promoted by periodic 79 movement of the wiper motor windshield.

80 Two simulation times were programmed: 4s (calibration) and 15 min (water slide test and 81 water and soil loss evaluations), as well as the monitoring of the electromagnetic pulses 82 emitted by the water flow sensor through of the programming language C. For coupling were used: Hardware Arduino Uno R3, software ARDUINO version 1.0.5 - R2, relay module, 83 84 momentary switch, protoboard and jumpers.

85 In determining the average diameter of drops was used the method of wheat flour [22]. For this, three trays with dimensions of 0.54 for 0.95 m were filled with a uniform layer of 2 cm 86 87 thick wheat flour, then the sprinkling water test on trays during 4 seconds with the rain 88 simulator [23, 24].

89 Drying of wheat flour was held in forced air circulation oven at 60° C for 24 hours and mesh sieves separated granules formed 2.000; 1.180; 0.425 and 0.300 mm. For determination of 90 91 average size (D50), weighed 2 grams of drops retained in each sieve [25], as shown in 92 Equation 1. Then the number of drops was determined by counting the granules deposited in each sieve with help of the softwares of image processing and analysis. 93

94

71 72 73

74 75

$$95 \qquad D_{50} = \sqrt[3]{\frac{6m}{\pi\rho}}$$

96

97 Where:

- 98  $D_{50}$  drop diameter (mm);
- 99 *m* drop average mass (mg);
- 100  $\rho$  density of water (mg mm<sup>-3</sup>).

101 The terminal velocity of the droplet (equation 2) and the kinetic energy of the drop by 102 Equation 3 estimated the impact of drops with the soil surface.

103  
104 
$$VT = \sqrt{\frac{9,81}{0,4671 \times D^{-0,9859}}}$$
 (Eq.2)  
105  
106 Where:  
107  $VT$  - terminal velocity of drop (m s<sup>-1</sup>).  
108  $E c/a = \frac{10^{-3}}{2} \rho \omega x L x V^2$  (Eq.3)  
109

- 110 Where:
- 111 *E c/a* droplet kinetic energy (J  $m^{-2}$ );
- 112  $\rho\omega$  water density (kg m<sup>-3</sup>);
- 113 *L* water average applied by nozzles (mm).

114

#### 115 **2.1 Analysis of the data**

116 117 Data were submitted to the Shapiro-Wilk (P > 0,01) and Levene (P > 0,01) tests, 118 respectively, to verify the homoscedasticity normality. When the hypothesis of the residual 119 homoscedasticity of the data was not true, the Kruskal-Wallis non-parametric statistical 120 method (P > 0,05) was used as a complement for multiple comparisons of Fisher-Bonferroni 121 test means (P > 0,05).

122 In the data analysis, the free software R Statistical 3.4.2® [26] was used. The parametric 123 and non-parametric statistical analysis were implemented, using functions available in the 124 ExpDes.pt [27] and agricolae packages [28]. To find the most appropriate transformation to 125 reach the approximately Gaussian behavior the Box-Cox transformation family was used 126 through the MASS package [29]. The construction of the graphs was performed by the 127 ggplot2 package [30].

128

#### 129 3. RESULTS AND DISCUSSION

130

Able Image Analyser, ImageJ and Safira did not show a significant difference in counting of 131 132 the number of drops (Figure 2). Each software was able to read different image formats, 133 converting file formats, processing and analyzing the images. The Able Image Analyser 134 software was not efficient in the practicality of use, due to the fact of having its license of 135 paid use. ImageJ and Safira software are free software. However, in terms of ease of implementation, ImageJ has a more accessible interface. According to [31], ImageJ provides 136 137 a powerful macro language to automate repetitive tasks. As ImageJ's source code opens. 138 you can also optimize existing functions and plugins for your own needs.



Figure 2. Number of drops counted by image analysis software. Mean followed by the same letter does not differ by Fisher - the 5% probability of Bonferroni.

142

139

The image processing technique can be successfully implemented for accurate drop size measurement [32]. The method of image processing can analyze a wide diameter range and despite the elimination of some data that were recorded in the image, the number of drops counted digitally is considered sufficient for the analysis [32, 33].

147 In the simulators, the wind is represented by the oscillations of the spout. Analyzing the 148 variables that refer to droplet size, such as average mass, diameter and volume, in the 149 oscillation of the spray nozzle of 21 min<sup>-1</sup> oscillations, the droplets presented larger sizes 150 (Figure 3).



Figure 3. Oscillations per minute of the water spray nozzle. Mean followed by the same letter does not
 differ by Fisher - the 5% probability of Bonferroni.

153 It was observed that in the oscillation factor, in the configuration obtaining larger droplets (21 154 oscillations min<sup>-1</sup>) the terminal velocity is also higher, where the rate of drop increases as the 155 droplet size increases [34].

The terminal speed is directly related to the kinetic energy of the drop (Eq. 3). For your time, the kinetic energy with which the drop reaches the soil is crucial to infer the erosive potential of that ground, since it is responsible for promoting the detachment of soil aggregates, thus causing the disposal of sediments, generating erosion.

160 In experiments to evaluate rainfall simulators, it is important to know the kinetic energy 161 values of the drops produced because one of the main applications of the equipment is in 162 the study of water erosion, so we must know the kinetic energy value of the simulated rain in 163 the studies of erosive process under laboratory conditions, since each kinetic energy value 164 provides different values of soil particles detachment, regardless of whether the rainfall is 165 simulated or natural. However, when working only with precipitation intensity, such an assertion could not be
 made, since there would be quite different impact energies between simulated and natural
 rainfall for the same intensity [35].

169 In the height factor of the equipment, the droplets presented larger sizes at the lower height 170 (2.12 m) (Figure 4). However, the kinetic energy per unit area had an inverse behavior, 171 showing higher values for higher equipment heights. There are larger drops, higher terminal

172 velocity as the height of the spray nozzle decreases, and higher kinetic energy value per unit



173 area as the height of the spray nozzle increases.

176

177 The range of drop sizes that can be observed was 1.2 mm to 3.1 mm, similar values were 178 obtained in the experiment [36], using a rain simulator.

179 The terminal speed is directly related to the size of the drop (Eq. 2). The small drops are 180 usually similar to natural speeds, to calm conditions vertical showers. Because the smallest

Figure 4. Height of the rainfall simulator. Means followed by the same letter do not differ by the Fisher Bonferroni test at 5% of error probability.

heights of fall, the larger falls have smaller terminal velocity compared to drops of rain that fall naturally and reach your maximum speed between 5.1 m s<sup>-1</sup> and 6 m s<sup>-1</sup>. The terminal velocity is directly related to the droplet size (Eq. 2). Small droplet speeds are generally similar to natural speeds, for vertical rains in calm conditions. Due to the smaller fall heights, larger falls have lower terminal velocities compared to naturally occurring raindrops reaching their maximum velocity between 5.1 m s<sup>-1</sup> and 6 m s<sup>-1</sup>.

# 188 **4. CONCLUSION**

189

187

Able Image Analyser, ImageJ and Safira did not show any significant difference in counting
of the number of drops. However, ImageJ software proved to be more suitable as a research
tool, since it has the license of free use and greater ease of use.

193 With the calibration of the rainfall simulator, the produced drops presented the necessary 194 standards so that the use of this equipment in water and soil loss practices may be valid.

195 Satisfactory results compared to natural rains are obtained in more than one combination of 196 height and oscillation.

197

# 198COMPETING INTERESTS

- 199
- 200 Authors have declared that no competing interests exist.

201 202

# 203 **REFERENCES**

- 204
- Dunkerley D. How is overland flow produced under intermittent rain? An analysis
   using plot-scale rainfall simulation on dryland soils. J Hydrol Elsevier B.V. 2018;
   556:119–30.
- 2082.Sobrinho TA, Carvalho DF De. Parâmetros físicos do solo e erosão hídrica sob209chuva simulada. Rev Bras Eng Agrícola e Ambient 2006; 10(2):261–68.
- Oliveira JR de. Perdas de Solo, Água e Nutrientes em um Argissolo Vermelho Amarelo sob Diferentes Padrões de Chuva Simulada. 2007[Online] Universidade
   Federal Rural do Rio de Janeiro 2007.
- 213 4. Zhao G, Mu X, Wen Z, et al. Soil Erosion Conservation, and Eco-Environment
  214 Changes in the Loess Plateau of China. L Degrad Dev 2013; 24(5):499–510.
- 215 5. D. Meyer L. Rainfall Simulators for Soil Conservation Research 1988;
- Schick J, Bertol I, Neroli PC, et al. Erodibilidade de um cambissolo húmico sob chuva natural. Rev Bras Cienc do Solo 2014; 38(6):1906–17.
- Lima PLT, Silva MLN, Curi N, et al. Soil loss by water erosion in areas under maize and jack beans intercropped and monocultures. Ciência e Agrotecnologia 2014; 38(2):129–39.
- 2218.Lima CA de, Palácio HA de Q, Andrade EM de, et al. Characteristics of rainfall and222erosion under natural conditions of land use in semiarid regions. Rev Bras Eng

- 223 Agrícola e Ambient 2013; 17(11):1222–29.
- 224 9. Cao L, Zhang K, Dai H, et al. Modeling Interrill Erosion on Unpaved Roads in the
  225 Loess Plateau of China. L Degrad Dev 2015; 26(8):825–32.
- Lassu T, Seeger M. The Wageningen Rainfall Simulator: Set-up and Calibration of an indoor Nozzle-Type Rainfall Simulator for Soil Erosion Studies. L Degrad Dev L 2015; 26(March):604–12.
- Wang N, Jiao J-Y, Lei D, et al. Effect of Rainfall Erosion: Seedling Damage and Establishment Problems. L Degrad Dev 2014; 25(6):565–72.
- Santos TEM dos, Montenegro AA de A, Silva Junior V de P e. Erosão Hídrica e
   Perda de Carbono Orgânico em Diferentes Tipos de Cobertura do Solo no Semi Árido, em Condições de Chuva Simulada. Rev Bras Recur Hídricos 2008; 13(2):113–
   25.
- 23513.Yakubu ML, Yusop Z. Adaptability of rainfall simulators as a research tool on urban236sealed surfaces a review. Hydrol Sci J Taylor & Francis 2017; 62(6):996–1012.

Polyakov VO, Nearing MA, Stone JJ, et al. Runoff and erosional responses to a
drought-induced shift in a desert grassland community composition. J Geophys Res
2010; 115(G4):G04027.

- Ramos JC, Bertol I, Barbosa FT, et al. Influência das condições de superfície e do cultivo do solo na erosão hídrica em um cambissolo húmico. Rev Bras Ciência do Solo 2014; 38(5):1587–600.
- Abrantes JRCB, Lima JLMP De, Montenegro AAA. Desempenho da modelagem cinemática do escoamento superficial para chuvas intermitentes em solos com cobertura morta. Rev Bras Eng Agrícola e Ambient 2015; 19(2):166–72.

 Hamed Y, Albergel J, Pépin Y, et al. Comparison between rainfall simulator erosion and observed reservoir sedimentation in an erosion-sensitive semiarid catchment. CATENA 2002; 50(1):1–16.

- 249 18. Santos MA do N dos, Panachuki E, Alves Sobrinho T, et al. Water Infiltration in an
  250 Ultisol After. Rev Bras Cienc do Solo 2014; 38(1):1612–20.
- 19. Danáčová M, Valent P, Výleta R. Evaluation of Surface Runoff Generation Processes
   Using a Rainfall Simulator: A Small Scale Laboratory Experiment. IOP Conf Ser
   Earth Environ Sci 2017; 95:022016.
- 254 20. Almeida WS de;, Carvalho DF de;, Panachuki E, et al. Erosão hídrica em diferentes sistemas de cultivo e níveis de cobertura do solo. Pesqui Agropecuária Bras 2016;
  256 51(9):1110–19.
- 257 21. Alvares CA, Stape JL, Sentelhas PC, et al. Köppen's climate classification map for
   258 Brazil. Meteorol Zeitschrift 2013; 22(6):711–28.
- 259 22. Hudson NW, of Conservation SRD, Extension. The Flour Pellet Method for
   260 Measuring the Size of Raindrops, 1964[Online] Department of Conservation and
   261 Extension 1964.

- 262 23. Sousa Júnior SF de, Mendes TA, Siqueira EQ de. Development and calibration of a
   263 rainfall simulator for hydrological studies. RBRH 2017; 22:59.
- 264 24. Carvalho M, Tarqui J, Silva V, et al. Avaliação do Funcionamento de um Simulador
  265 de Chuva Pelo Método da Farinha. Rev Bras Recur Hídricos 2012; 17(3):115–24.
- 266 25. Meyer LD, Harmon WC. Interrill Runoff and Erosion: Effects of Row-sideslope Shape,
   267 Rain Energy, and Rain Intensity. Trans ASAE 1992; 35(4):1199–203.
- 268 26. R Core Team. R: A Language and Environment for Statistical Computing.
   269 2018[Online] Vienna, Austria 2018.
- 270 27. Ferreira EB, Cavalcanti PP, Nogueira DA. ExpDes.pt: Pacote Experimental Designs
   271 (Portuguese). 2018[Online] 2018.
- 272 28. Mendiburu F de. agricolae: Statistical Procedures for Agricultural Research.
  273 2019[Online] 2019.
- 274 29. Venables WN, Ripley BD. MASS: Support Functions and Datasets for Venables and
   275 Ripley's MASS. 2018[Online] 2018.
- 276 30. Wickham H. ggplot2, Media 2009[Online] Springer New York: New York, NY 2009.
- Pennekamp F, Schtickzelle N. Implementing image analysis in laboratory-based
   experimental systems for ecology and evolution: a hands-on guide. Methods Ecol
   Evol 2013; 4(5):483–92.
- Sudheer K., Panda R. Digital image processing for determining drop sizes from
   irrigation spray nozzles. Agric Water Manag 2000; 45(2):159–67.
- Hu B, Angeli P, Matar OK, et al. Evaluation of drop size distribution from chord length
   measurements. AIChE J 2006; 52(3):931–39.
- 34. Kavian A, Mohammadi M, Cerda A, et al. Simulated raindrop's characteristic
  measurements. A new approach of image processing tested under laboratory rainfall
  simulation. CATENA Elsevier 2018; 167(August):190–97.
- 35. Amorim RSS, Silva DD da, Pruski FF, et al. Influência da declividade do solo e da
  energia cinética de chuvas simuladas no processo de erosão entre sulcos. Rev Bras
  Eng Agrícola e Ambient 2001; 5(1):124–30.
- 290 36. Pérez-Latorre FJ, Castro L de, Delgado A. A comparison of two variable intensity
   291 rainfall simulators for runoff studies. Soil Tillage Res Elsevier B.V. 2010; 107(1):11–
   292 16.

293